


## Withstands extreme ambient temperature changes and holds true accuracy



- Withstands extreme ambient temperature changes •
- Maintains accuracy with thermal shock
- High pressure and vacuum compatible
- Drift free
- Rugged housing
- Specifications

| Specifications                     |  |  |  |  |
|------------------------------------|--|--|--|--|
| Sensing Range                      | -50 to 1200°F (-45 to 650°C)   |  |  |  |
| Ambient Temperature Range          | -50 to 212°F (-45 to 100°C)  |  |  |  |
| Storage Temperature Range          | -50 to 212°F (-45 °C to 100°C)   |  |  |  |
| Field of View of Sensing Element   | approximately 3:1 (17°)  |  |  |  |
| Minimum Spot size                  | 6 mm (0.25")   |  |  |  |
| Dominant Spectral Response         | 6.5 to 14 μm   |  |  |  |
| Output Sensor                      | K type thermocouple  |  |  |  |
| Impedance                          | 4-8 Kohms  |  |  |  |
| Emissivity (e)                     | 0.90   |  |  |  |
| Measurement Type                   | Thermopile   |  |  |  |
| Resolution                         | Approximately 0.00018°C, Johnson Noise                                 |  |  |  |
| Response Time (95% of step change) | 100 milliseconds   |  |  |  |
| Accuracy (Interchangeability)      | 1% to factory calibration conditions                                   |  |  |  |
| Dimensions                         | See above  |  |  |  |
| Housing                            | Stainless Steel 303  |  |  |  |
| Cable Assembly                     | 10 feet of twisted shielded pair of base thermocouple material, teflon |  |  |  |
|                                    | sheathed, type K, 24 AWG, rated to 392°F (200°C)                       |  |  |  |
| Humidity                           | Non-Condensing   |  |  |  |
| Power Requirements                 | None   |  |  |  |
| Environmental                      | Hermetically sealed, exceeds NEMA 4X, IP67, Intrinsically Safe,        |  |  |  |
|                                    | CE and RoHS rated  |  |  |  |

- Self poweredReliable
- K type thermocouple output
- Fast response time

## omega.com®

\_\_\_\_\_ CEOMEGA®\_\_

OMEGAnet<sup>®</sup> Online Service omega.com Internet e-mail info@omega.com

|   |  | 0                        |  | 0  |  |  |
|---|--|--------------------------|--|--|--|--|
| Servicing North America:  |  |                          | Servicing Europe:  |  |  |  |
| U.S.A.:<br>ISO 9001 Certified   | One Omega Drive, Box 4047<br>Stamford, CT 06907-0047<br>Tel: (203) 359-1660<br>FAX: (203) 359-7700<br>e-mail: info@omega.com |                          | Czech Republic: Frystatska 184, 733 01 Karviná, Czech Republic<br>Tel: +420 (0)59 6311899<br>FAX: +420 (0)59 6311114<br>Toll Free: 0800-1-66342<br>e-mail: info@omegashop.cz |  |  |  |
| Canada:   | 976 Bergar<br>Laval (Quebec) H7L 5A1, Canada<br>Tel: (514) 856-6928<br>FAX: (514) 856-6886<br>e-mail: info@omega.ca          | Gern                     | nany/Austria:  | Daimlerstrasse 26,<br>Tel: +49 (0)7056 93<br>FAX: +49 (0)7056 9<br>Toll Free in Germa<br>e-mail: info@omeg | 398-29<br>ny: 0800 639 7678  |  |
| For immediate technical or application assistance:  |  |                          | United Kingdom: One Omega Drive, River Bend Technology Centre<br>ISO 9002 Certified Northbank, Irlam, Manchester   |  |  |  |
| U.S.A. and Canada: Sales Service: 1-800-826-6342/1-800-TC-OMEGA®<br>Customer Service: 1-800-622-2378/1-800-622-BEST®<br>Engineering Service: 1-800-872-9436/1-800-USA-WHEN® |  | C-OMEGA®<br>00-622-BEST® |  | M44 5BD United Kingdom<br>Tel: +44 (0)161 777 6611<br>FAX: +44 (0)161 777 6622                             |  |  |
| Mexico:   | En Español: (001) 203-359-7803<br>FAX: (001) 203-359-7807<br>e-mail:espanol@omega.com<br>info@omega.com.mx                   |                          |  |  | foll Free in United Kingdom: 0800-488-488<br>mail: sales@omega.co.uk |  |

It is the policy of OMEGA Engineering, Inc. to comply with all worldwide safety and EMC/EMI regulations that apply. OMEGA is constantly pursuing certification of its products to the European New Approach Directives. OMEGA will add the CE mark to every appropriate device upon certification. The information contained in this document is believed to be correct, but OMEGA accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. WARNING: These products are not designed for use in. and should not be used for human applications.

USA

## WARRANTY/DISCLAIMER

OMEGA ENGINEERING, INC. warrants this unit to be free of defects in materials and workmanship for a period of **25 months** from date of purchase. OMEGA's WARRANTY adds an additional one (1) month grace period to the normal **two (2) year product warranty** to cover handling and shipping time. This ensures that OMEGA's customers receive maximum coverage on each product.

If the unit malfunctions, it must be returned to the factory for evaluation. OMEGA's Customer Service Department will issue an Authorized Return (AR) number immediately upon phone or written request. Upon examination by OMEGA, if the unit is found to be defective, it will be repaired or replaced at no charge. OMEGA's WARRANTY does not apply to defects resulting from any action of the purchaser, including but not limited to mishandling, improper interfacing, operation outside of design limits, improper repair, or unauthorized modification. This WARRANTY is VOID if the unit shows evidence of having been tampered with or shows evidence of having been damaged as a result of excessive corrosion; or current, heat, moisture or vibration; improper specification; misupplication; misuse or other operating conditions outside of OMEGA's control. Components in which wear is not warranted, include but are not limited to contact points, fuses, and triacs.

OMEGA is pleased to offer suggestions on the use of its various products. However, OMEGA neither assumes responsibility for any omissions or errors nor assumes liability for any damages that result from the use of its products in accordance with information provided by OMEGA, either verbal or written. OMEGA warrants only that the parts manufactured by the company will be as specified and free of defects. OMEGA MAKES NO OTHER WARRANTIES OR REPRESENTATIONS OF ANY KIND WHATSOEVER, EXPRESSED OR IMPLIED, EXCEPT THAT OF TITLE, AND ALL IMPLIED WARRANTIES INCLUDING ANY WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. LIMITATION OF LIABILITY: The remedies of purchaser set forth herein are exclusive, and the total liability of OMEGA with respect to this order, whether based on contract, warranty, negligence, indemnification, strict liability or otherwise, shall not exceed the purchase price of the component upon which liability is based. In no event shall OMEGA be liable for consequential, incidental or special damages.

CONDITIONS: Equipment sold by OMEGA is not intended to be used, nor shall it be used: (1) as a "Basic Component" under 10 CFR 21 (NRC), used in or with any nuclear installation or activity; or (2) in medical applications or used on humans. Should any Product(s) be used in or with any nuclear installation or activity, medical application, used on humans, or misused in any way, OMEGA assumes no responsibility as set forth in our basic WARRANTY/DISCLAIMER language, and, additionally, purchaser will indemnify OMEGA and hold OMEGA harmless from any liability or damage whatsoever arising out of the use of the Product(s) in such a manner.

## RETURN REQUESTS / INQUIRIES

Direct all warranty and repair requests/inquiries to the OMEGA Customer Service Department. BEFORE RETURNING ANY PRODUCT(S) TO OMEGA, PURCHASER MUST OBTAIN AN AUTHORIZED RETURN (AR) NUMBER FROM OMEGA'S CUSTOMER SERVICE DEPARTMENT (IN ORDER TO AVOID PROCESSING DELAYS). The assigned AR number should then be marked on the outside of the return package and on any correspondence.

The purchaser is responsible for shipping charges, freight, insurance and proper packaging to prevent breakage in transit.

FOR **WARRANTY** RETURNS, please have the following information available BEFORE contacting OMEGA:

- 1. Purchase Order number under which the product was PURCHASED,
- 2. Model and serial number of the product under warranty, and
- 3. Repair instructions and/or specific problems relative to the product.

FOR **NON-WARRANTY** REPAIRS, consult OMEGA for current repair charges. Have the following information available BEFORE contacting OMEGA:

- 1. Purchase Order number to cover the COST of the repair,
- 2. Model and serial number of the product, and
- 3. Repair instructions and/or specific problems relative to the product.

OMEGA's policy is to make running changes, not model changes, whenever an improvement is possible. This affords our customers the latest in technology and engineering. OMEGA is a registered trademark of OMEGA ENGINEERING, INC.

© Copyright 2008 OMEGA ENGINEERING, INC. All rights reserved. This document may not be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form, in whole or in part, without the prior written consent of OMEGA ENGINEERING, INC.