


1/8 DIN Ultra Compact Case, Temperature, Process and Strain PID Controllers




CNi8C Series



CNi8C33, shown smaller than actual size.

- Ultra Compact 1/8 DIN Controller
- Full Autotune PID Control
- Built-In Excitation
- NEMA 4 (IP65) Bezel
- RS232, RS422/485 Communication, Menu Selectable

The ultra-compact CNi8C and CNi8SC controllers are similar to the full size CNi8 in an ultra-compact enclosure. Only 51 mm (2") behind the panel.



Options

Ordering Suffix	Description
-AL	Limit alarm version (alarms only, no PID control)* ²
-SM	Simplified menu (on/off control or alarms, no PID)* ³
Network Options	
-C24	Isolated RS232 and RS485/422, 300 to 19.2 Kb* ¹
Power Supply	
	Standard power input: 90 to 240 Vac/dc, 50 to 400 Hz (no entry required)
-DC	12 to 36 Vdc, 24 Vac* ¹
Factory Setup	
-FS	Factory setup and configuration
-FS(RTD-1N)	Customized CNiS model for MIL-T-7990B nickel RTD input, 0 to 200°C (32 to 392°F)
-FS(RTD-2N)	Customized CNiS model for MIL-T-7990B nickel RTD input, -40 to 300°C (-40 to 572°F)
Software (Requires Network Option)	
OPC-SERVER LICENSE	OPC server/driver software license

*¹ "-DC" and "-C24" not available with excitation.
 *² Analog output is not available with "-AL" units.
 *³ "-SM" option not available on CNiS strain models.

To Order

Model No.	Output 1	Output 2
1/8 DIN Compact Case with 2 Control Outputs		
CNi8C33	Relay	Relay
CNi8C34	Relay	DC pulse
CNi8C44	DC pulse	DC pulse
CNi8C22	0.5 A SSR	0.5 A SSR
CNi8C23	0.5 A SSR	Relay
CNi8C24	0.5 A SSR	DC pulse
CNi8C53	Analog	Relay
CNi8C54	Analog	DC pulse
CNi8C52	Analog	0.5 A SSR
1/8 DIN Compact Case Strain/Process Input with 2 Control Outputs		
CNi8C33	Relay	Relay
CNi8C44	DC pulse	DC pulse
CNi8C43	DC pulse	Relay
CNi8C42	DC pulse	0.5 A SSR
CNi8C22	0.5 A SSR	0.5 A SSR
CNi8C23	0.5 A SSR	Relay
CNi8C24	0.5 A SSR	DC pulse
CNi8C53	Analog	Relay
CNi8C54	Analog	DC pulse
CNi8C52	Analog	0.5 A SSR

Comes complete with operator's manual.

Ordering Examples: CNi8C33, 1/8 DIN compact universal temperature process controller with 2 relay outputs.

iSeries Common Specifications (All i/8, i/16, i/32 DIN)

Universal Temperature and Process Input (DPi/CNi Models)

Accuracy: $\pm 0.5^{\circ}\text{C}$ temp; 0.03% rdg

Resolution: $1^{\circ}/0.1^{\circ}$; $10\ \mu\text{V}$ process

Temperature Stability:

RTD: $0.04^{\circ}\text{C}/^{\circ}\text{C}$

TC @ 25°C (77°F): $0.05^{\circ}\text{C}/^{\circ}\text{C}$

Cold Junction Compensation

Process: 50 ppm/ $^{\circ}\text{C}$

NMRR: 60 dB

CMRR: 120 dB

A/D Conversion: Dual slope

Reading Rate: 3 samples/s

Digital Filter: Programmable

Display: 4-digit 9-segment LED

10.2 mm (0.40"); i32, i16, i16D, i8DV

21 mm (0.83"); i8 10.2 mm (0.40") and

21 mm (0.83"); i8DH **RED, GREEN,**

and **AMBER** programmable colors for process variable, setpoint and temperature units

Input Types: Thermocouple, RTD, analog voltage, analog current

Thermocouple Lead Resistance: 100 Ω max

Thermocouple Types (ITS 90):

J, K, T, E, R, S, B, C, N, L (J DIN)

RTD Input (ITS 68): 100/500/1000 Ω Pt sensor, 2-, 3- or 4-wire; 0.00385 or 0.00392 curve

Voltage Input: 0 to 100 mV, 0 to 1V, 0 to 10 Vdc

Input Impedance: 10 M Ω for 100 mV 1 M Ω for 1 or 10 Vdc

Current Input: 0 to 20 mA (5 Ω load)

Configuration: Single-ended

Polarity: Unipolar

Step Response: 0.7 sec for 99.9%

Decimal Selection:

Temperature: None, 0.1

Process: None, 0.1, 0.01 or 0.001

Setpoint Adjustment:

-1999 to 9999 counts

Span Adjustment:

0.001 to 9999 counts

Offset Adjustment: -1999 to 9999

Excitation (Not Included with

Communication): 24 Vdc @ 25 mA (not available for low-power option)

Universal Strain and Process Input (DPiS/CNiS Models)

Accuracy: 0.03% reading

Resolution: 10/1 μV

Temperature Stability: 50 ppm/ $^{\circ}\text{C}$

NMRR: 60 dB

CMRR: 120 dB

A/D Conversion: Dual slope

Reading Rate: 3 samples/s

Digital Filter: Programmable

Input Types: Analog voltage and current

Voltage Input: 0 to 100 mVdc, -100 mVdc to 1 Vdc, 0 to 10 Vdc

Input Impedance: 10 M Ω for 100 mV; 1 M Ω for 1V or 10 Vdc

Current Input: 0 to 20 mA (5 Ω load)

Linearization Points: Up to 10

Configuration: Single-ended

Polarity: Unipolar

Step Response: 0.7 sec for 99.9%

Decimal Selection: None, 0.1, 0.01 or 0.001

Setpoint Adjustment:

-1999 to 9999 counts

Span Adjustment: 0.001 to 9999 counts

Offset Adjustment: -1999 to 9999

Excitation (Optional In Place Of Communication): 5 Vdc @ 40 mA; 10 Vdc @ 60 mA

Control

Action: Reverse (heat) or direct (cool)

Modes: Time and amplitude proportional control; selectable manual or auto PID, proportional, proportional with integral, proportional with derivative and anti-reset Windup, and on/off

Rate: 0 to 399.9 s

Reset: 0 to 3999 s

Cycle Time: 1 to 199 s; set to 0 for on/off

Gain: 0.5 to 100% of span; setpoints 1 or 2

Damping: 0000 to 0008

Soak: 00.00 to 99.59 (HH:MM), or OFF

Ramp to Setpoint:

00.00 to 99.59 (HH:MM), or OFF

Auto Tune: Operator initiated from front panel

Control Output 1 and 2

Relay: 250 Vac or 30 Vdc @ 3 A (resistive load); configurable for on/off, PID and ramp and soak

Output 1: SPDT, can be configured as alarm 1 output

Output 2: SPDT, can be configured as alarm 2 output

SSR: 20 to 265 Vac @ 0.05 to 0.5 A (resistive load); continuous

DC Pulse: Non-isolated; 10 Vdc @ 20 mA

Analog Output (Output 1 Only):

Non-isolated, proportional 0 to 10 Vdc or 0 to 20 mA; 500 Ω max

Output 3 Retransmission:

Isolated Analog Voltage and Current

Current: 10 V max @ 20 mA output

Voltage: 20 mA max for 0 to 10 V output

Network and Communications

Ethernet: Standards compliance IEEE 802.3 10 Base-T

Supported Protocols: TCP/IP, ARP, HTTPGET

RS232/RS422/RS485: Selectable from menu; both ASCII and MODBUS protocol selectable from menu; programmable 300 to 19.2 Kb; complete programmable setup capability; program to transmit current display, alarm status, min/max, actual measured input value and status

RS485: Addressable from 0 to 199

Connection: Screw terminals

Alarm 1 and 2 (Programmable)

Type: Same as output 1 and 2

Operation: High/low, above/below, band, latch/unlatch, normally open/normally closed and process/deviation; front panel configurations

Analog Output (Programmable):

Non-isolated, retransmission 0 to 10 Vdc or 0 to 20 mA, 500 Ω max (output 1 only); accuracy is $\pm 1\%$ of FS when following conditions are satisfied: input is not scaled below 1% of input FS, analog output is not scaled below 3% of output FS

General

Power: 90 to 240 Vac $\pm 10\%$, 50 to 400 Hz*, 110 to 300 Vdc, equivalent voltage

Low Voltage Power Option: 24 Vac**, 12 to 36 Vdc for DPi/CNi/DPiS/CNiS; 20 to 36 Vdc for dual display, ethernet and isolated analog output from qualified safety approved source

Isolation

Power to Input/Output: 2300 Vac per 1 minute test

For Low Voltage Power Option: 1500 Vac per 1 minute test

Power to Relay/SSR Output:

2300 Vac per 1 minute test

Relay/SSR to Relay/SSR Output:

2300 Vac per 1 minute test

RS232/485 to Input/Output:

500 Vac per 1 minute test

Environmental Conditions:

All Models: 0 to 55°C (32 to 131°F)

90% RH non-condensing

Dual Display Models:

0 to 50°C (32 to 122°F), 90% RH

non-condensing (for UL only)

Protection:

DPi/CNi/DPiS/CNiS32,16,16D, 8C:

NEMA 4X/Type 4 (IP65) front bezel

DPi/CNi/DPiS/CNiS8, 8DH, 8DV:

NEMA 1/Type 1 front bezel

Approvals: UL, C-UL, CE per

2014/35/EU.

Dimensions

i/8 Series: 48 H x 96 W x 127 mm D

(1.89 x 3.78 x 5")

i/16 Series: 48 H x 48 W x 127 mm D

(1.89 x 1.89 x 5")

i/32 Series: 25.4 H x 48 W x 127 mm D

(1.0 x 1.89 x 5")

Panel Cutout

i/8 Series: 45 H x 92 mm W

(1.772 x 3.622"), $\frac{1}{8}$ DIN

i/16 Series: 45 mm (1.772") square,

$\frac{1}{16}$ DIN

i/32 Series: 22.5 H x 45 mm W

(0.886 x 1.772"), $\frac{1}{32}$ DIN

Weight

i/8 Series: 295 g (0.65 lb)

i/16 Series: 159 g (0.35 lb)

i/32 Series: 127 g (0.28 lb)

* No CE compliance above 60 Hz.

** Units can be powered safely with 24 Vac power, but no certification for CE/UL are claimed.