



STANDARD
PX6000C0-015AV,
with 1/4 NPT male port,
shown actual size.

STANDARD MODELS

To Order			
Models with MS33656-4 Pressure Connection, Integral Connector & mV/V Output			
RANGE		MODEL NO.	COMPATIBLE METERS*
psi	bar		
VACUUM			
30 to 0 (inHg)	-1 to 0	PX6000L1-30VACV	DP41-S, DP25B-S
ABSOLUTE PRESSURE			
0 to 15	0 to 1.0	PX6000L1-015AV	DP41-S, DP25B-S
0 to 20	0 to 1.4	PX6000L1-020AV	DP41-S, DP25B-S
0 to 50	0 to 3.4	PX6000L1-050AV	DP41-S, DP25B-S
0 to 100	0 to 6.9	PX6000L1-100AV	DP41-S, DP25B-S
0 to 200	0 to 13.8	PX6000L1-200AV	DP41-S, DP25B-S
0 to 300	0 to 20.7	PX6000L1-300AV	DP41-S, DP25B-S
GAGE PRESSURE			
0 to 15	0 to 1.0	PX6000L1-015GV	DP41-S, DP25B-S
0 to 20	0 to 1.4	PX6000L1-020GV	DP41-S, DP25B-S
0 to 50	0 to 3.4	PX6000L1-050GV	DP41-S, DP25B-S
0 to 100	0 to 6.9	PX6000L1-100GV	DP41-S, DP25B-S
0 to 200	0 to 13.8	PX6000L1-200GV	DP41-S, DP25B-S
0 to 300	0 to 20.7	PX6000L1-300GV	DP41-S, DP25B-S

Comes complete with 5-point NIST traceable calibration.

* Visit us online for compatible meters.

Ordering Example: PX6000L1-050GV, 50 psi gage pressure transducer with PTIH-10-6P electrical connection and MS33656-4 male pressure port. PTS06A-10-6S-R, mating connector (sold separately).

ACCESSORY

MODEL NO.	DESCRIPTION
PTS06A-10-6S-R	Mating connector for PX6000 units with PTIH-10-6P electrical connection



METRIC
PXM6000MC6-004BARAV,
shown installed,
smaller than actual size.

METRIC MODELS

To Order			
Models with G 1/4 Male Pressure Connection, Cable or mini DIN and mV/V Output			
RANGE		MODEL NO.	COMPATIBLE METERS*
ABSOLUTE PRESSURE			
0 to 1 bar	0 to 15 psi	PXM6000MC[*]-001BARAV	DP41-S, DP25B-S
0 to 1.60 bar	0 to 23 psi	PXM6000MC[*]-1.60BARAV	DP41-S, DP25B-S
0 to 4 bar	0 to 58 psi	PXM6000MC[*]-004BARAV	DP41-S, DP25B-S
0 to 6 bar	0 to 87 psi	PXM6000MC[*]-006BARAV	DP41-S, DP25B-S
0 to 10 bar	0 to 145 psi	PXM6000MC[*]-010BARAV	DP41-S, DP25B-S
0 to 16 bar	0 to 232 psi	PXM6000MC[*]-016BARAV	DP41-S, DP25B-S
GAGE PRESSURE			
0 to 1 bar	0 to 15 psi	PXM6000MC[*]-001BARGV	DP41-S, DP25B-S
0 to 1.60 bar	0 to 23 psi	PXM6000MC[*]-1.60BARGV	DP41-S, DP25B-S
0 to 4 bar	0 to 58 psi	PXM6000MC[*]-004BARGV	DP41-S, DP25B-S
0 to 6 bar	0 to 87 psi	PXM6000MC[*]-006BARGV	DP41-S, DP25B-S
0 to 10 bar	0 to 145 psi	PXM6000MC[*]-010BARGV	DP41-S, DP25B-S
0 to 16 bar	0 to 232 psi	PXM6000MC[*]-016BARGV	DP41-S, DP25B-S
0 to 25 bar	0 to 319 psi	PXM6000MC[*]-025BARGV	DP41-S, DP25B-S

Comes complete with 5-point calibration.

* Visit us online for compatible meters.

[*] = Insert "0" for 0.6 m (2') cable or "6" for mini DIN connector.

Ordering Example: PXM6000MC0-004BARGV, 4 bar gage pressure transducer with 0.6 m (2') cable and G 1/4 male pressure port.