

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.
 H315 + H320 Causes skin and eye irritation.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs (Central nervous system, Liver, Kidney, Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
 P403 + P235 Store in a well-ventilated place. Keep cool.

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Silicone resin

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Xylene	1330-20-7	>= 30 - < 50
Ethylbenzene	100-41-4	>= 10 - < 20
Linseed Oil	8001-26-1	>= 1 - < 5
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 1 - < 5
Naphthalene	91-20-3	>= 0.1 - < 1
Zinc octoate	136-53-8	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention.
 Rinse mouth thoroughly with water.

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

- Most important symptoms and effects, both acute and delayed : Causes skin and eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Dry chemical
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
-

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : Ensure all equipment is electrically grounded before beginning transfer operations.
This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations.
Restrict flow velocity in order to reduce the accumulation of static electricity.
- Local/Total ventilation : Use with local exhaust ventilation.
Use only in an area equipped with explosion proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapors or spray mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
-

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Organic peroxides
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	NIOSH REL
Linseed Oil	8001-26-1	ST	125 ppm 545 mg/m3	NIOSH REL
		TWA (mist - total)	10 mg/m3	NIOSH REL
		TWA (mist - respirable)	5 mg/m3	NIOSH REL
Solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (as total hydrocarbon vapor)	ACGIH
Naphthalene	91-20-3	TWA	10 ppm	ACGIH

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	NIOSH REL
		ST	15 ppm 75 mg/m ³	NIOSH REL
		TWA	10 ppm 50 mg/m ³	OSHA Z-1

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Zinc octoate	136-53-8

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 Use only in an area equipped with explosion proof exhaust ventilation.
 Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

- | | | |
|--------------------------|---|---|
| Material | : | Antistatic gloves

Impervious gloves

Flame retardant gloves |
| Remarks | : | Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |
| Eye protection | : | Wear the following personal protective equipment:
Safety goggles |
| Skin and body protection | : | Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Hygiene measures | : | Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|----------------|---|-------------------|
| Appearance | : | liquid |
| Color | : | brown |
| Odor | : | solvent |
| Odor Threshold | : | No data available |
| pH | : | No data available |

DOW CORNING(R) RSN-0997 RESIN

Version Revision Date: MSDS Number: Date of last issue: -
1.0 12/16/2014 956098-00001 Date of first issue: 12/16/2014

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 130 °C

Flash point : 25 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.002

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, kinematic : 105 cSt

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : Flammable liquid and vapor.

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

fions

Vapors may form explosive mixture with air.
Can react with strong oxidizing agents.
When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. Safe handling conditions may be maintained by keeping vapor concentrations within the occupational exposure limit for formaldehyde.
Formaldehyde may cause cancer. It is also toxic by inhalation, skin absorption and ingestion, corrosive to skin and eyes, and may cause skin sensitization and respiratory irritation.
See OSHA formaldehyde standard, 29 CFR 1910.1048
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Handling operations that can promote accumulation of static charges.
Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products
Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 26.17 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 3,142 mg/kg
Method: Calculation method

Ingredients:

Xylene:
Acute oral toxicity : LD50 (Rat): 4,300 mg/kg

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate : 11 mg/l
 Test atmosphere: vapor
 Method: Expert judgment
 Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate : 1,100 mg/kg
 Method: Expert judgment
 Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.2 mg/l
 Exposure time: 4 h
 Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Solvent naphtha (petroleum), heavy arom.:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
 Exposure time: 4 h
 Test atmosphere: vapor
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: The substance or mixture has no acute dermal toxicity

Naphthalene:

Acute oral toxicity : LD50 (Mouse): 553 mg/kg
 Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l
 Exposure time: 4 h
 Test atmosphere: vapor
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,500 mg/kg
 Assessment: The substance or mixture has no acute dermal toxicity

Zinc octoate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
Date of first issue: 12/16/2014

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.2 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Ingredients:**Xylene:**

Species: Rabbit

Result: Skin irritation

Solvent naphtha (petroleum), heavy arom.:

Assessment: Repeated exposure may cause skin dryness or cracking.

Naphthalene:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Zinc octoate:

Species: Guinea pig

Result: Skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Ingredients:**Xylene:**

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Ethylbenzene:

Species: Rabbit

Result: No eye irritation

Solvent naphtha (petroleum), heavy arom.:

Species: Rabbit

Result: No eye irritation

Naphthalene:

Species: Guinea pig

Result: No eye irritation

Method: OECD Test Guideline 405

Zinc octoate:

Species: Rabbit

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Result: Irritation to eyes, reversing within 21 days
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.
Respiratory sensitization: Not classified based on available information.

Ingredients:**Xylene:**

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Ethylbenzene:

Test Type: Human repeat insult patch test (HRIPT)
Routes of exposure: Skin contact
Result: negative

Solvent naphtha (petroleum), heavy arom.:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Naphthalene:

Test Type: Maximization Test (GPMT)
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Zinc octoate:

Test Type: Maximization Test (GPMT)
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Xylene:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative
	: Test Type: In vitro sister chromatid exchange assay in mammalian cells

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
 Test species: Mouse
 Application Route: Skin contact
 Result: negative

Ethylbenzene:
 Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
 Result: negative

: Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
 mammalian liver cells in vivo
 Test species: Mouse
 Application Route: Inhalation
 Method: OECD Test Guideline 486
 Result: negative

Linseed Oil:
 Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Solvent naphtha (petroleum), heavy arom.:
 Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
 cytogenetic test, chromosomal analysis)
 Test species: Rat
 Application Route: Intraperitoneal injection
 Result: negative

Naphthalene:
 Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

: Test Type: Chromosome aberration test in vitro
 Result: positive

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
 mammalian liver cells in vivo
 Test species: Rat
 Application Route: Ingestion
 Result: negative

Zinc octoate:
 Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

DOW CORNING(R) RSN-0997 RESIN

Version 1.0	Revision Date: 12/16/2014	MSDS Number: 956098-00001	Date of last issue: - Date of first issue: 12/16/2014
----------------	------------------------------	------------------------------	--

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Test species: Mouse
 Application Route: Ingestion
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Ingredients:**Xylene:**

Species: Rat
 Application Route: Ingestion
 Exposure time: 103 weeks
 Result: negative

Ethylbenzene:

Species: Rat
 Application Route: Inhalation
 Exposure time: 104 weeks
 Result: positive
 Remarks: The mechanism or mode of action may not be relevant in humans.

Solvent naphtha (petroleum), heavy arom.:

Species: Rat
 Application Route: inhalation (vapor)
 Exposure time: 105 weeks
 Result: positive
 Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Naphthalene:

Species: Rat
 Application Route: inhalation (vapor)
 Exposure time: 105 weeks
 Result: positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC

Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

Naphthalene 91-20-3

OSHA

No ingredient of this product present at levels greater than or

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Reasonably anticipated to be a human carcinogen

Naphthalene

91-20-3

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Ingredients:**Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Solvent naphtha (petroleum), heavy arom.:

Effects on fertility : Test Type: Fertility
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Naphthalene:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Result: negative

Zinc octoate:

Effects on fertility

: Test Type: Two-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

Effects on fetal development

: Test Type: Embryo-fetal development
 Species: Rabbit
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

Reproductive toxicity - Assessment

: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT-single exposure

May cause respiratory irritation.

Ingredients:**Xylene:**

Assessment: May cause respiratory irritation.

Solvent naphtha (petroleum), heavy arom.:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Liver, Kidney, Auditory system) through prolonged or repeated exposure.

Ingredients:**Xylene:**

Routes of exposure: inhalation (vapor)

Target Organs: Central nervous system, Liver, Kidney

Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg//6h/d.

Ethylbenzene:

Routes of exposure: inhalation (vapor)

Target Organs: Auditory system

Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg//6h/d.

Solvent naphtha (petroleum), heavy arom.:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Naphthalene:

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity**Ingredients:****Xylene:**

Species: Rat

NOAEL: 4.35 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 d

Ethylbenzene:

Species: Rat, female

LOAEL: 75 ppm

Application Route: inhalation (vapor)

Exposure time: 104 w

Solvent naphtha (petroleum), heavy arom.:

Species: Rat

NOAEL: 750 mg/kg

Application Route: Ingestion

Exposure time: 21 w

Naphthalene:

Species: Mouse

NOAEL: 133 mg/kg

Application Route: Ingestion

Exposure time: 90 d

Method: OECD Test Guideline 408

Species: Rat

NOAEL: 0.011 mg/l

Application Route: inhalation (vapor)

Exposure time: 13 w

Method: OECD Test Guideline 413

Species: Rat

NOAEL: 300 mg/kg

Application Route: Skin contact

Exposure time: 13 w

Method: OECD Test Guideline 411

Zinc octoate:

Species: Rat

NOAEL: 234 mg/kg

Application Route: Ingestion

Exposure time: 90 d

Method: OECD Test Guideline 408

Remarks: Based on data from similar materials

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)); 0.96 mg/l
Exposure time: 7 d

Toxicity to bacteria : EC50 (Nitrosomonas sp.); 96 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 209

Solvent naphtha (petroleum), heavy arom.:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)); 2 - 5 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)); 1.4 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)); > 1 - 3 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)); 0.48 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Naphthalene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)); 6.08 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)); 2.16 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)); 0.4 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)); 0.37 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia pulex (Water flea)); 0.59 mg/l
Exposure time: 125 d

Toxicity to bacteria : IC50 (Nitrosomonas sp.); 29 mg/l
Exposure time: 24 h

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Zinc octoate:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 0.78 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 1.22 mg/l
 Exposure time: 48 h
 Remarks: Based on data from similar materials

Toxicity to algae : NOEC (*Pseudokirchneriella subcapitata* (green algae)): 5.2 µg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (*Oncorhynchus mykiss* (rainbow trout)): 0.199 mg/l
 Exposure time: 30 d
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 0.048 - 0.156 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability**Ingredients:****Xylene:**

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 87.8 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F
 Remarks: Based on data from similar materials

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 - 80 %
 Exposure time: 28 d

Naphthalene:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 %
 Exposure time: 4 Weeks
 Method: OECD Test Guideline 302

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Zinc octoate:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301D
 Remarks: Based on data from similar materials

Bioaccumulative potential**Ingredients:****Xylene:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
 Bioconcentration factor (BCF): 5.4 - 25.9

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.2

Ethylbenzene:

Bioaccumulation : Species: Fish
 Bioconcentration factor (BCF): < 100
 Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 3.6

Naphthalene:

Bioaccumulation : Species: Cyprinus carpio (Carp)
 Bioconcentration factor (BCF): 36.5 - 168
 Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 3.4

Zinc octoate:

Partition coefficient: n-octanol/water : log Pow: > 5.7

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

Waste Code	:	D001: Ignitability D018
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulation

UNRTDG

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (Ethylbenzene, Xylene)
Class	:	3
Packing group	:	III
Labels	:	3

IATA-DGR

UN/ID No.	:	UN 1993
Proper shipping name	:	Flammable liquid, n.o.s. (Ethylbenzene, Xylene)
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (Ethylbenzene, Xylene)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

UN/ID/NA number : UN 1993
 Proper shipping name : FLAMMABLE LIQUIDS, N.O.S.
 (Ethylbenzene, Xylene)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	286
Ethylbenzene	100-41-4	1000	9091
Naphthalene	91-20-3	100	21739

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
 Acute Health Hazard
 Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Xylene	1330-20-7	35 %
Ethylbenzene	100-41-4	11 %
Naphthalene	91-20-3	0.46 %

US State Regulations**Pennsylvania Right To Know**

Dimethyl, methyl, phenyl, phenylmethyl silicone resin	68037-66-1	30 - 50 %
Xylene	1330-20-7	30 - 50 %
Ethylbenzene	100-41-4	10 - 20 %
Linseed Oil	8001-26-1	1 - 5 %
Solvent naphtha (petroleum), heavy arom.	64742-94-5	1 - 5 %
Naphthalene	91-20-3	0.1 - 1 %

DOW CORNING(R) RSN-0997 RESIN

Version 1.0	Revision Date: 12/16/2014	MSDS Number: 956098-00001	Date of last issue: - Date of first issue: 12/16/2014
----------------	------------------------------	------------------------------	--

Toluene	108-88-3	0 - 0.1 %
1,2,4-Trimethylbenzene	95-63-6	0 - 0.1 %
2-(2-Butoxyethoxy)ethanol	112-34-5	0 - 0.1 %

New Jersey Right To Know

Dimethyl, methyl, phenyl, phenylmethyl sili- cone resin	68037-66-1	30 - 50 %
Xylene	1330-20-7	30 - 50 %
Ethylbenzene	100-41-4	10 - 20 %
Linseed Oil	8001-26-1	1 - 5 %
Solvent naphtha (petroleum), heavy arom.	64742-94-5	1 - 5 %
Naphthalene	91-20-3	0.1 - 1 %

California Prop 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

Ethylbenzene	100-41-4
Naphthalene	91-20-3
Aniline	62-53-3

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Toluene	108-88-3
---------	----------

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

PICCS : All ingredients listed or exempt.

KECI : All ingredients listed, exempt or notified.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.

IECSC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).


REACH : Consult your local Dow Corning office.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

DOW CORNING(R) RSN-0997 RESIN

Version 1.0 Revision Date: 12/16/2014 MSDS Number: 956098-00001 Date of last issue: -
 Date of first issue: 12/16/2014

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/16/2014

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.



DOW CORNING(R) RSN-0997 RESIN

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	12/16/2014	956098-00001	Date of first issue: 12/16/2014

US / Z8