Part# CC BINDER SDS-0064L CC HIGH TEMP (LIQUID)

SAFETY DATA SHEET



Date issued : 05/07/2015 SDS number : SCC-029L Date revised : 07/07/2023 Revision number : 6

Page 1 of 5

29L Low Expansion Cement, Liquid

1. Identification

Product code: 29L

Product identifier: 29L Low Expansion Cement, Liquid Product description: Low Expansion Cement, Liquid Product formulation name: 29L Low Expansion Cement, Liquid Chemical family: Sodium Silicate Solution

Manufacturer / Supplier

Sauereisen 160 Gamma Drive Pittsburgh, PA 15238 Emergency contact: John Kozak Emergency Phone: (800)444-8235 Alternate Contact: Anthony Comport Customer Service: 412 963-0303 E-Mail: jakozak@sauereisen.com

Emergency telephone number (24 hour)

Poison Control Center (Medical):1-800-222-1222 CHEMTREC (US Transportation): 1-800-424-9300 CHEMTREC (Canada Transportation):1-703-527-3887

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Respiratory Tract Irritation, Category 3 Skin Irritation, Category 2 Eye Irritation, Category 2B

Environmental hazards:

Acute Hazards to the Aquatic Environment, Category 3

Label elements



Signal word: WARNING

Hazard statement(s)

H320: Causes eye irritation. H315: Causes skin irritation. H335: May cause respiratory irritation. H402: Harmful to aquatic life.

Precautionary statement(s)

Prevention:

P264: Wash ... thoroughly after handling. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water/...

P332+P313: If skin irritation occurs: Get medical advice/attention.

P322: Specific measures (see ... on this label).

P362: Take off contaminated clothing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/national regulations.

Potential health effects

Eye: Contact causes eye irritation.

Skin: Itching or burning will occur with repeated or prolonged contact. May exacerbate existing skin conditions.

Inhalation: Causes sneezing and burning or itching in nose and throat.

3. Composition/information on ingredients

| Chemical name | % w/w | CAS No. |
|---------------------|-------|-----------|
| Sodium Polysilicate | < 50 | 1344-09-8 |
| Water | < 50 | 7732-18-5 |

4. First-aid measures

Eye: Check for and remove all contact lenses. Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Do not use eye ointment. Seek medical attention.

Skin: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

Ingestion: If Swallowed, do not induce vomiting. Immediately drink two large glasses of water or activated charcoal slurry. Seek Medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Not expected to be a problem.

Additional information: Note: To prepare activated charcoal slurry, add 50 grams of activated charcoal to 400 ml of water and mix well.

5. Fire-fighting measures

Flammable class: NA = Not Applicable

Explosion hazards: NA = Not Applicable

Fire fighting procedures: NA = Not Applicable

Fire explosion: NA = Not Applicable

Sensitivity to static discharge: None

Sensitivity to mechanical impact: None

6. Accidental release measures

Small spill: Clean-Up Procedure: Spill area may become slippery; use care to avoid falls. Flush spill area with plenty of water.

Large spill: For spill greater than 100 gallons; isolate, dike and store discharged material, if possible. Collect with dry sand, clay or other absorbent. Flushed cleaned areas with water. Observe Environmental regulations. Wear PPE - gloves, rubber boots, and safety glasses.

7. Handling and storage

General procedures: Avoid contact with eyes, skin and clothing.

For Industrial Use only! Do not take internally. May cause irritation. Wear chemical splash goggles, gloves and protective clothing. Wash throughly after handling.

Conditions for safe storage: Store in a cool, dry place.

Keep container closed when not in use. Keep away from food and drinking water.

Always mix well before using.

8. Exposure controls/personal protection

Appropriate engineering controls: Normal ventilation for good working conditions should be used.

Individual protection measures, such as personal protective equipment

Eye / face protection: Chemical resistant goggles and/or face shield.

Skin protection - hand protection: Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, longsleeved workclothes. Synthetic apron. Boots. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

Respiratory protection: Use NIOSH approved mist respirator where spray occurs. For emergencies, a self contained breathing apparatus or a full-face respirator is recommended. If TLV of any component is exceeded, use appropriate respiratory protection or ventilate in accordance with OSHA Regulation 29 CFR 1910.

9. Physical and chemical properties

Appearance: Liquid Color: Hazy to clear Odor: No appreciable odor. Odor threshold: NA = Not Applicable **pH:** 11 to 12 Melting point: (32°F) Freezing point: (32°F) Initial boiling point and boiling range: (212°F) Flash point: NA = Not Applicable Evaporation rate (n-butyl acetate = 1): < 1 Lower explosion limit / flammability limit: 0 Upper explosion limit / flammability limit: 0 Vapor pressure: Vapor is water Relative vapor density: Same as water vapor. Relative density: 1.26 to 1.39 Solubility: 100 % Percent volatiles: NA = Not Applicable

10. Stability and reactivity

Reactivity: Yes

Dangerous polymerization: No

Chemical stability: Stable under normal conditions of use and storage.

Conditions to avoid: Flammable hydrogen gas may be produced on prolonged contact with metals such as Aluminum, tin, lead, and zinc.

Hazardous decomposition products: None known.

Incompatible materials: Materials to avoid: Acids, salts, or alcohols may cause gel formation (non-hazardous).

11. Toxicological information

Acute toxicity

Acute dermal toxicity LD₅₀: No data available.

Acute oral toxicity LD₅₀: No data available.

Acute inhalation toxicity LC₅₀: No data available.

Serious eye damage / irritation: Eye, Skin and Inhallation Irritant.

Carcinogenicity

Notes: Does not contain any substances greater than 0.1% listed by IARC (Internationa Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union)

12. Ecological information

Aquatic toxicity, both acute and chronic: Sodium Silicate has low toxicity. TLM 96 hr in mosquitofish is 2,320 mg/L. High pH (alkalinity) of undiluted material is harmful to aquatic life.

13. Disposal considerations

Disposal methods: Comply with federal, state and local regulations. If approved, flush with water to chemical sewer. For large quantities, neutralize with dilute acid and landfill solids or flush neutral liquid to sewer with plenty of water.

Empty container: Disposal must be made according to official regulations.

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: Not Regulated

Technical name: NA = Not Applicable

Transport hazard class(es): Not Regulated

15. Regulatory information

UNITED STATES

Dot label symbol and hazard classification

R36/37/38: Irritating to eyes, respiratory system and skin.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S7/8: Keep container tightly closed and dry.

SARA Section 311/312 Hazard Categories

311/312 Health hazards: Irritant.

313 reportable ingredients: There are no listed chemicals above detection limits in this compound.

Title III notes: None above detection limits.

TSCA (The Toxic Substances Control Act)

| Chemical name | CAS No. |
|---------------------|-----------|
| Sodium Polysilicate | 1344-09-8 |
| Water | 7732-18-5 |

California Proposition 65: Known to the State of California to cause cancer or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low level prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of the hazardous / carcinogenic ingredients listed elsewhere in the SDS comply with State of California regulations.



R36/37/38: Irritating to eyes, respiratory system and skin. S24/25: Avoid contact with skin and eyes. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S7/8: Keep container tightly closed and dry.

WHMIS Classification: Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL): Components included on inventory

16. Other information

Prepared by: John A Kozak Date revised: 07/07/2023

Revision summary: This SDS replaces the 07/29/2021 SDS. Revised: **Section 2:** Classification of the substance or mixture, Label elements, Precautionary statement(s).

| HMIS rating | | | |
|---------------------|---|--|--|
| Health | 2 | | |
| Flammability | 0 | | |
| Physical hazard | 0 | | |
| Personal protection | В | | |